oro audio

MR115/MR115N MRseries MR115A/MR115NA

Two-way Loudspeaker System



**FEATURES** 

plywood housing

High quality components, high strength

Can be placed on stage, can be hung

Small height, take small space

高质量单元配置,高强度夹板箱体高度尺寸小,占用空间小可舞台摆放、可吊挂


Applications: Stage monitor


MR115 is compact, small height size, coaxial ,15" two-way full range monitor series speaker with different configurations, has balanced and real sound quality. Configuration:1x15" high efficency mid-bass unit and 1x1" exit throat 44mm voice coil HF driver with special designed horn. The cabinet is made of multilayer composite plywood with wear-resistant polyurea paint. The model with N is a neodymium magnetic unit, and the model with A is active.

MR115是不同配置,15"同轴结构设计的两分音舞台监听系列音箱,结构紧凑,高度尺寸小,音质平衡衡、真实。单元配置:1只15"高效率中低音单元和1只1"喉口44芯驱动器,配置专门设计的号角。箱体采用多层复合夹板,聚脲喷涂制作。型号带N为钕磁单元、型号带A为有源。



### **CONFIGURATION**





适用范围 ●舞台监听

产品特征

# MR115/ MR115N

70Hz-18kHz 65Hz-20kHz

 $1\times15$ "(385mm)/3"voice coil LF  $1\times1$ "(25mm)/1.7"voice coil HF

400W RMS,1600W peak

97dB 1watt/1 metre

124dB continuous,130dB peak

8 ohms nominal

 $70^{\circ} \times 40^{\circ}$ 

2.2kHz passive

2×Speakon NL4

 $610mm \times 460mm \times 635mm$ 

26 kg/pc; 22 kg/pc 31 kg/pc; 27 kg/pc

## MR115A/ MR115NA

70Hz-18KHz 65Hz-20kHz

 $1\times15$ "(385mm)/3"voice coil LF  $1\times1$ "(25mm) / 1.7"voice coil HF

600W/8Ω

124dB continuous,130dB peak

70° × 40°

---

INPUT TYPE: Balanced Differential line

 $610mm \times 460mm \times 635mm$ 

28 kg/pc; 24kg/pc 33 kg/pc; 29kg/pc

### MODEL

FREQUENCY RESPONSE(-3dB)
FREQUENCY RESPONSE(-10dB)
DRIVERS

RATED POWER
SENSITIVITY
MAXIMUM SPL
IMPEDANCE
DISPERSION(-6dB)
CROSSOVER FREQUENCIES
INPUT CONNECTORS
PACKAGE SIZE
NET WEIGHT
GROSS WEIGHT

www.fdbaudio.com Page 30