

CM70-IP

Avonic PTZ Camera 20x Zoom IP

The Avonic CM70 is a premium-quality PTZ camera that includes a rich feature set usually found only on broadcast-grade cameras including PoE, low latency 3G-SDI and balanced audio embedding.

Optional premium features consist of SRT streaming, a Tally light and a customizable Color Matrix.

The camera with IP, HDMI and 3G-SDI outputs is designed for fixed installations and works very well in low light conditions.

The camera is equipped with high quality components like a Panasonic high SNR CMOS sensor with digital noise reduction and a High Quality glass lens. Control the camera over IP, RS232 or RS485 with any controller with VISCA or PELCO support.



Features

Lens

High-quality glass lens, 20x optical zoom and 55.2° horizontal field of view.

Low light

High SNR CMOS combined with digital noise reduction for a clear picture even under very low light conditions.

Full HD 1080p60

The camera has a Full HD resolution of 1920 x 1080p60 and achieves a pristine image quality.

IP-features

The camera can be powered using PoE (802.3af) and can be accessed by webGUI, controlled by VISCA over IP/Onvif and stream the video.

DUAL low latency IP-Stream

H265, H264, optional SRT and MJPEG compression at a bitrate up to 40Mbit enabling Full HD video stream by ultra-low latency over RTSP, RTMP, UDP, Unicast and Multicast.

Outputs

3G-SDI, HDMI, USB 2.0 (1080p30) and IP.

Control

Control the camera with common protocols: VISCA, Pelco-D/P via RS232, RS485, IP(VISCA), Onvif or IR, remote control included. Supports up to 255 presets with 0.1° accuracy and High Speed Pan Tilt function.

Audio embedding

Balanced audio input with embedding into IP stream, SDI and HDMI outputs. Includes configurable audio offset.

Optional Premium features

SRT streaming, Tally light, configurable Color Matrix. License AV-LC70-1 sold separately.

Applications

- Education
- Churches
- Video Conferencing
- Healthcare
- Broadcasting
- Courtroom
- Live Events
- And more

SPECIFICATIONS

Camera

Video Systems	1920x1080/ 1280x720 p60/ 50/ 30/ 25/ 59.94/ 29.97 i60/ 50/ 59.94
Sensor	1/3" CMOS, 2.12mp, 16:9
Shutter	Auto, Manual, 1/25 ~1/10000
Scanning mode	Progressive, Interlaced (not over IP)
Zoom/Aperture/Focal length	20x optical/ F1.8-F11/ 4.4-88.8 mm
Minimal Illumination	0.05 LUX
White Balance	Auto, Manual, OnePush, 2400K-7100K in steps of 100K
Backlight Compensation	supported
Digital Noise Reduction	2D & 3D DNR
Signal Noise Ratio	>55 dB
Horizontal FOV wide ~ tele	55.2° ~ 3.2°
Vertical FOV wide ~tele	42.1° ~ 2.4°
Horizontal rotation	-170° ~ +170°
Vertical rotation	-30° ~ +90°
Pan speed range	1.7 ~ 100°/s
Tilt speed range	1.7 ~ 70°/s
H&V image flip	supported
Number of presets	255
Preset accuracy	0.1

IP features

Video coding standard	H.265 / H.264 / MJPEG
H.265 Profiles	main
H.264 Profiles	main, base, high
Main stream resolution	1920x1080 / 1280x720
Main stream max frame rate	60fps
Main stream bitrate	64 ~ 40960 Kbps
Sub stream resolution	320x180 / 320x240 / 640x360 / 1280x720 / 1920x1080
Sub stream max frame rate	30fps
Sub stream bitrate	64 ~ 40960 Kbps
Video bitrate type	Variable, Fixed
Support protocols	RTSP, RTMP, ONVIF, SRT, Multicast, Unicast
Audio standard	AAC / mp3 / G.711A
Audio bitrate	32, 64, 96, 128 Kbps
Audio sample rate	16, 32, 44.1, 48 Khz
Audio line in	balanced audio line in via 5-way Phoenix connector.

Input/Output Interface

HDMI output	1.4
SDI output	3G-SDI, SMPTE 425M level A, 10-bit YCbCr 4:2:2
USB Output	USB 2.0 (max. 1080p30)
Network interface	RJ45 100 Mbit
Serial communication	RS232 mini DIN-8, RS485 2pin Phoenix
Serial control protocol	VISCA, PELCO-P, PELCO-D
IP control protocol	VISCA OVER IP, Onvif

General specifications

Input voltage	12V
PoE	PoE 12W (802.3af)
Power consumption	12W
Power supply	12V2A
Power connector	EIAJ-4 - Philmore 255 plug
Operating temperature	-5°C ~ 40°C
Storage temperature	-20°C ~ 60°C
Operating humidity	20% ~ 95% non-condensing
Bottom fastening screw thread	1/4" 20 UNC
Color	Black, White
Dimensions product wxhxd	133 x 180 x 149 mm. excl. connectors
Weight product	1.5 kg
Dimensions box	26 x 24 x 24 cm
Weight box	2.4 kg
Included	power adapter, remote control, RS232 cable, RS485 2-way Phoenix connector, Balanced Audio Line-In 5-way Phoenix connector

Versions

Black	CM70-IP-B
White	CM70-IP-W

